


SPECIFICATIONS
2005 SALEEN S281 3-VALVE

GENERAL	Coupe	Convertible
Curb Weight, lb.	est 3550	NA
Weight Distribution, F/R	53/47	NA
Fuel Capacity, gal.		15.7
Wheelbase, in.		107.1
Track, F/R		63.9/62.8
Width		74.0
Length		189.1
Height	56.0	NA
Trunk Space, cubic ft.	12.3	NA

ENGINE

Type	4.6L, 3V, SOHC V-8
Bore and Stroke	3.55 x 3.54 in.
Displacement	4.6 liters, 281 cu in.
Accessory Pulleys	Saleen Underdrive Pulleys
Exhaust System	Saleen Stainless, 2.5 in. Variable Exhaust
Horsepower	325 bhp @ 5200 RPM
Torque	340 lb-ft @ 4500 RPM
Fuel	Premium Unleaded 91 Octane

DRIVETRAIN

Transmission, standard	Saleen Quick Ratio 5-Speed Transmission
Transmission, optional	5-Speed Electronically Controlled Automatic
8.8 in. Differential; 3.55:1 Ratio	Standard; Manual Transmission
8.8 in. Differential; 3.31:1 Ratio	Standard; Automatic Transmission
Saleen MaxGrip Speed-Sensitive Limited Slip	Optional

SUSPENSION

Front	MacPherson strut with lower control arm; Saleen Racecraft system including N2 struts with linear-rate coil-over springs; 1.38-in. tubular stabilizer (anti-roll) bar with urethane pivot bushings; specially calibrated suspension settings
Rear	Live axle located by three links plus a Panhard rod; Saleen Racecraft system including direct-acting, linear-rate coil springs and N2 shocks; 0.79-in. stabilizer (anti-roll) bar; specially calibrated suspension settings

BRAKES

Power Assisted 4-Wheel ABS Brakes	
12.4 in. Dual Piston Vented Disc (Front)	Standard
11.8 in. Disc (Rear)	
Saleen ABS 4-Piston Calipers	
14.0 in. Slotted and Vented Disc (Front)	Optional

WHEELS AND TIRES

Saleen Seven Spoke Alloy Wheels	
20 in. x 9 in. Front	Standard
20 in. x 9 in. Rear	Standard
20 in. x 10 in. Rear	Optional
High-Performance Radials	
P275/35ZR20 (Front)	Standard
P275/35ZR20 (Rear)	Standard
Ultra-High-Performance Pirelli P-Zero Rosso Upgrade	
P275/35ZR20 (Front)	Optional
P275/40ZR20 (Rear)	Optional